


Vivo Pro Flood light



Features

• Energy savings of up to 90 % compared to halogen lamp floodlights





• Energy savings of up to 45 % compared to luminaires that use conventional discharge lamps



• Homogeneous luminance distribution and reduced glare

Colour Rendering Index

≥80

IP Rating

• Bright, robust and durable



Vivo Pro

TECHNICAL DATA SHEET - VIVO PRO - 14107 - FLOOD LIGHT











TECHNICAL DATA

Product Data Flood Light PHILIPS LED Lamp Type

200W Wattage 6000K **Color Temperature** Rated Luminaire Luminous Flux 20000lm **Rated Luminaire Efficiency** 100lm/W **IP Rating** 65 100° **Beam Angle**

AC220-240V Voltage Frequency Range 50-60 Hz CRI Ra>80 **Power Factor** >0.95


Operating Temperature -20 °C to +50 °C

Class I **Safety Class**

Material Aluminum alloy+ Clear glass


Finish Black 50,000 Hours Life Span Warranty 5 Years


Applications Outdoors, Commercial, Hospitality etc.













TECHNICAL OPTIONS

| Wattage | 10W/50W |
|-------------------|---------------------------------------|
| Color Temperature | 3000K - 6000K |
| Control | Switchable, 1-10V, DALI, TRIAC, 0-10V |