

DelgadoRecessed Downlight



Features

• Selected LED chip with efficient driver, energysaving with 50000 hours lifespan







• Excellent heat dissipation design

Powder coated surface treatment, durable and not easy to fall off







Delgado

TECHNICAL DATA SHEET - DELGADO - 15064 - RECESSED DOWNLIGHT











TECHNICAL DATA

Product Data Recessed Downlight SAMSUNG LED **Lamp Type**


30W Wattage 3000K **Color Temperature** Rated Luminaire Luminous Flux 2400lm **Rated Luminaire Efficiency** 80lm/W IP Rating 44 90° Beam Angle

AC220-240V Voltage 50-60 Hz Frequency Range CRI Ra>80 >0.95 **Power Factor** SDCM(Macadam step) < 6 **Output Current** 700mA THD (%) ≤ 15% **Safety Class** Class II -20°C ~ +40°C **Operating Temperature**

25°C **Storage Temperature** Aluminum with Powder coated surface Material **Finish** White + Iron Grey 60,000 Hours Life Span 6 Years Warranty **Applications** Residential, Commercial, Hospitality etc.


TECHNICAL OPTIONS

Wattage	9W / 15W / 20W
Color Temperature	3000K-6000K
Control	Switchable/TRIAC/0-10V/DALI/1-10V









Cutout: 200x200mm

