

# **Cerco**Recessed Moon light



# **Features**

- · High brightness, adopting high quality
- SMD 2835 LED
- Enery saving up to 85%, high efficiency power supply, low powerconsumption
- Provides a white and homogenous ambient lighting that recreates natural daylight
- Thin&light design achieves high performance and low cost
- Diffuser: PMMA





# TECHNICAL DATA SHEET - CERCO - 15373 - RECESSED MOON LIGHT











### **TECHNICAL DATA**

**Product Data** Recessed light SAMSUNG LED **Lamp Type** Driver **OSRAM Driver** 

40W Wattage 4000K **Color Temperature** Rated Luminaire Luminous Flux 3400lm **Rated Luminaire Efficiency** 85lm/W **IP Rating** 42 120° **Beam Angle** 


Voltage AC220-240V 50-60 Hz **Frequency Range** CRI Ra>80 >0.9 **Power Factor** 1000mA **Output Current Safety Class** Class II SDCM(MacAdam) < 3

-20°C ~ +40°C **Operating Temperature** 

PMMA Diffuser + Aluminium Material


**Finish** White Life Span 50,000 Hours 5 Years Warranty

**Applications** Residential, Commercial, Hospitality etc.









## **TECHNICAL OPTIONS**

Wattage Color Temperature	25W, 90W, 150W 3000K-6000K
Control	Switchable, TRIAC, 1-10V, Dali, 0-10V