

Techar Wall Light



Features

- Extruded aluminum alloy #6063; Powder coating ,T= 60~80 um.
- Painting: class 1/ASTM class 4B
- Reflector: Optical reflector. efficiency $\geq$ 85%
- UV-Resistance PC T=8mm



Wall



IK Rating
IK10



IP Rating
IP65






Standard Warranty

TECHNICAL DATA SHEET - TECHAR - 15408 - WALL LIGHT



TECHNICAL DATA

Product Data	Wall light
Lamp Type	Nichia LED
Wattage	25W
Color Temperature	3000K
Rated Luminaire Luminous Flux	2412lm
Rated Luminaire Efficiency	96.5lm/W
IP Rating	65
Beam Angle	22°
Voltage	AC220-240V
Frequency Range	50-60 Hz
CRI	Ra>80
Power Factor	>0.5
Output Current	146mA
IK Rating	10
Working Temperature	-20°C ~+50°C
Safety Class	Class I
SDCM (MacAdam)	<5
Material	Aluminium Alloy + Optical Reflector
Finish	Dark Grey
Life Span	50,000 Hours
Warranty	5 Years
Applications	Outdoors, Residential, Commercial, Hospitality etc.



TECHNICAL OPTIONS

Wattage	4.5W/10W/18W/40W
Color Temperature	3000K-6000K
Beam Angle	10° / 38°
Finish	Black / Grey / White
Control	Switchable, TRIAC, PWM, 1-10V, DALI

