


Aina **Recessed Downlight**



Features

• High brightness, Low SDCM<3, low light



decline • High efficacy, high illuminance, accurate beam



IP Rating IP44

angle makes comfortable illumination atmosphere • Exterior driver triac dimmable (200-240v input) and 1-10v Dimmable (100-240v input)



• Easy installation, for wide applications

Colour Rendering Index ≥80



Standard Warranty



TECHNICAL DATA SHEET - AINA - 16571 - RECESSED DOWNLIGHT











TECHNICAL DATA

Product Data Recessed Downlight

CITIZEN LED **Lamp Type** Driver Meanwell Driver

70W Wattage 5700K **Color Temperature** Rated Luminaire Luminous Flux 8,400lm **Rated Luminaire Efficiency** 120lm/W **IP Rating** 44 **Beam Angle** 55°

Voltage AC220-240V 50-60 Hz **Frequency Range** CRI Ra>80 >0.95 **Power Factor** Safety Class Class III **Operating Temperature** -20°C ~ +50°C

SDCM(Macadam step) < 3

Material Pure Aluminium Heat Sink


+Shiny Reflector

Finish White Life Span 60,000 Hours 6 Years Warranty

Applications Residential, Commercial, Hospitality etc.


TECHNICAL OPTIONS

Wattage	22W, 28W, 38W, 60W,
Color Temperature	3000K-5000K
Beam Angle	25°, 45°, 50°
Finish	Silver, Black
Control	TRIAC, DALI, 1-10V










Cutout: 210-220mm



Beam Angle=55°