

Ostra **Ceiling light**



Features

• Ostra adopts high lumen SMD2835 LED, high light Surface transmission polycarbonate diffuser with even light output



Colour Rendering Index ≥80

• It is competitive in quality and price with energy saving more than 75%-90%



Standard Warranty



TECHNICAL DATA SHEET - OSTRA - 16823 - CEILING LIGHT











TECHNICAL DATA

Product Data Ceiling light

PHILIPS SMD 2835 LED **Lamp Type**

LIFUD DRIVER Driver

10W Wattage **Color Temperature** 3000K Rated Luminaire Luminous Flux 900lm 90lm/W **Rated Luminaire Efficiency IP Rating** 54 Beam Angle 120° 230V AC Voltage 50-60 Hz **Frequency Range** CRI Ra>80

Operating Temperature -20°C ~ +40°C Material Polycarbonate Body

Finish White


Life Span 50,000 Hours

Warranty 5 Years

Applications Residential, Commercial, Hospitality etc.

>0.5

A+









230mm

TECHNICAL OPTIONS

Power Factor

Energy Efficiency Class

Control	Switchable, 0-10V, 1-10V, TRIAC, DALI
Color Temperature	2700K - 6500K
Wattage	18W / 24W

Optional **Emergency Kit**