

Chico Recessed Downlight (Changeable CCT)



Features

• Up to 70% energy saving compared to standard CFL



IP Rating

IP44



UGR

- CCT Changeable/Adjustable
- 90° wide beam angle
- No UV/IR light
- Environment friendly, without Mercury or any other hazardous substances
- Easy to install



Standard Warranty



Chico

TECHNICAL DATA SHEET - CHICO - 17074 - RECESSED DOWNLIGHT (CHANGEABLE CCT)











TECHNICAL DATA

Product Data Recessed Downlight SAMSUNG LED **Lamp Type** Driver **Eaglerise Driver**

20W Wattage

3000K,4000K,6000K **Color Temperature** Rated Luminaire Luminous Flux 1800lm, 2000lm, 2200lm **Rated Luminaire Efficiency** 90lm/W, 100lm/W, 110lm/W


IP Rating 90° **Beam Angle**

Voltage AC220-240V 50-60 Hz **Frequency Range** CRI Ra>90 >0.95 **Power Factor** <3 SDCM(Macadam step) **Output Current** 500mA **Safety Class** Class II **Operating Temperature** -20°C ~ +40°C

White Aluminium Housing Material


Finish White Life Span 60,000 Hours 6 Years Warranty

Residential, Commercial, Hospitality etc. **Applications**









Cutout: 158mm

TECHNICAL OPTIONS

10W / 30W Wattage

Control Switchable/TRIAC/0-10V/DALI/1-10V

Optional **Emergency Kit**