

Moreno Recessed Trimless Spotlight (Tiltable)



Features

- Aluminium die casting material, improvment of the traditional heat sink, avoid the potential risk from high temperature
- Electrostatic painting surface, keep the color consistency
- Superior quality PC cover
- High light transmittance and optical soft, without astigmatism





UGR <19







Moreno

TECHNICAL DATA SHEET - MORENO - 17963 - RECESSED TRIMLESS SPOTLIGHT











TECHNICAL DATA

Product Data Recessed Trimless Spotlight

Lamp Type CITIZEN LED Driver **Tridonic Driver**

Wattage 10W 3000K **Color Temperature** Rated Luminaire Luminous Flux 600lm **Rated Luminaire Efficiency** 60lm/W IP Rating 44 **Beam Angle** 36°

Voltage AC220-240V Frequency Range 50-60 Hz Ra>90 CRI **Power Factor** >0.95 **Output Voltage** 32-40V **Output Current** 250mA Safety Class Class II THD ≤ 15%

Operating Temperature -20°C ~ +40°C


25°C **Storage Temperature** SDCM(MacAdam) < 3

Material Die Cast Aluminum body **Finish** White + Iron Gray Life Span 60,000 Hours Warranty 6 Years

Applications Residential, Commercial, Hospitality etc.


TECHNICAL OPTIONS

Wattage	12W
Color Temperature	2700K-6000K
Beam Angle	11°/15°/18°/24°/50°
Control	Switchable/TRIAC/DALI/1-10V/0-10V









Cutout: 70mm

