

## Flex

### Track Linear Lighting System - Tilttable (3 wire - 1 phase)



#### Features


- Flex T-Line LED Track Linear Light features a tiltable lighting panel, 3/4/6 wire track rail compatibility, customizable lighting effects, and multiple power channel selection, making it the ideal LED linear light fixture solution for various space lighting needs.



UGR  
<19



IP Rating  
IP20



Light  
Distribution

5  
years  
warranty

Standard Warranty

#### Configuration





Pendant

## TECHNICAL DATA SHEET - FLEX - 18656 - TRACK LINEAR LIGHTING SYSTEM



### TECHNICAL DATA

Product Data	Suspended Mounted
Lamp Type	SAMSUNG LED
Wattage	35W/40W/45W/50W
Color Temperature	6000K
Rated Luminaire Efficiency	160lm/W
IP Rating	20
Beam Angle	30°
Input Voltage	AC220-240V
Output Voltage	30 - 36V
Frequency Range	50-60 Hz
CRI	Ra>80
Power Factor	>0.9
Output Current	330mA
Surge voltage	2.5KV
Operating temperature	-25°C ~ +50°C
Storage humidity	10% - 80%
SDCM	<3
Flicker metric Pst LM	<1.0
Stroboscopic effect metric SVM	<0.4
Material	Aluminum, PC
Finish	White
Life Span	50,000 Hours
Warranty	5 Years
Applications	Residential, Hospitality, Commercial, etc.



### TECHNICAL OPTIONS

Color Temperature	2700K-6500K
Beam Angle	SP60°, NR90°
Control	Switchable, TRIAC, 1-10V, DALI, 0-10V
Finish	Black
Accessories	Suspension Kit, End Cap, Connector

## TECHNICAL DATA SHEET - FLEX - 18656 - TRACK LINEAR LIGHTING SYSTEM

### FLEXIBLE SOLUTION



Flexible combination of spotlight and linear track.

The position of the track linear can move freely through the rail, by adjusting the lock position

Different diffuser lenses for different lighting distributions



Narrow 60°



Wide 90°



Flat 120°

**Twin wings** can be tiltable individually or simultaneously through 30° while the central linear light can't be tilted



Optic angle:30° x 30°  
Tilting:0°



Optic angle:30° x 30°  
Tilting:30°



Optic angle:30° x 90°  
Tilting:0°



Optic angle:30° x 90°  
Tilting:30°

