

Britto

Street & Area Post-Top Light



Features

- Housing: Made of cast aluminum and iron with treatment of corrosion protection & UV-proof powder coating
- Diffuser: Opal Polycarbonate
- Fastener: 304 Stainless Steel



Installation
Street



IK Rating
IK08



IP Rating
IP65





Standard Warranty

TECHNICAL DATA SHEET - BRITTO - 19003 - STREET & AREA & POST-TOP LIGHT



TECHNICAL DATA

Product Data	Area & Post-top
Lamp Type	OSRAM LED
Wattage	50W
Color Temperature	4000K
Rated Luminaire Efficiency	5000lm
Rated Luminaire Flux	100lm/W
IP Rating	65
Voltage	AC90-260V
Frequency Range	50/60Hz
CRI	Ra>80
Power Factor	>0.9
Operating Temperature	-20°C ~ +50°C
Safety Class	Class II
SDCM (MacAdam)	<3
IK Rating	08
Material	Aluminium Body + Opal PC + Hot-dip galvanized iron pole
Finish	Matt Black UV Proof powder coating
Life Span	50,000 Hours
Warranty	5 Years
Applications	Outdoors, Residential, Commercial, Hospitality etc.



TECHNICAL OPTIONS

Color Temperature	3000K - 6000K
Finish	Dark Grey, Sand Silver, Gray Metal Sand Grain
Optional	Switchable, TRIAC, DALI, 0-10V, 1-10V

TECHNICAL DATA SHEET - BRITTO - 19003 - STREET & AREA & POST-TOP LIGHT

DIMENSIONS

