

Lenora Waterproof Luminaire (Changeable CCT & Wattage)



Features

- High Lumen Efficiency 125LM/W
- Flicker free driver
- Full PCB board and the diffuser is a whole part, no need to take the PCB apart but wire directly, much easier than the normal design
- Cables can be from the back or the two ends of the light, easy wiring
- Easy clips, one step assembly



IP Rating



warranty





Lenora

TECHNICAL DATA SHEET - LENORA - 19056 - WATERPROOF FIXTURE





TECHNICAL DATA

Product Data Lamp Type Wattage Color Temperature Rated Luminaire Efficiency IP Rating	Waterproof Luminaire BRIDGELUX LED 24W/32W/40W 3000K/4000K/6000K 125Im/W 65	LED	
Beam Angle Voltage Frequency Range CRI Power Factor Operating Temperature SDCM Safety Class	120° AC220-240V 50-60 Hz Ra>80 >0.5 -20°C ~ +50°C <6 Class I		1200mm
Material Finish Life Span Warranty Applications	Polycarbonate material White 50,000 Hours 5 Years Outdoors, Residential, Comme	ercial, Hospitality etc.	80mm 76mm

TECHNICAL OPTIONS

Installation	Suspension Mount
Control	Switchable, TRIAC, 1-10V, Dali
Optional	Emergency Kit, Microwave Sensor