

LinecoWaterproof Luminaire



Features

 High-end professional light, with high quality lever and up to 60% energy saving compare to T8





- Simple and quick installation, and maintenance-free
- Save up to 60% in electricity consumption compared to fluorescent lighting fixture
- Lightweight body material .corrosion resistant, waterproof and dustproof







Lineco

TECHNICAL DATA SHEET - LINECO - 16531 - WATERPROOF FIXTURE WITH MICROWAVE SENSOR





TECHNICAL DATA

Product Data Waterproof Luminaire

SMD2835 LED Lamp Type

40W Wattage **Color Temperature** 6500K Rated Luminaire Luminous Flux 4800lm 120lm/W **Rated Luminaire Efficiency**

IP Rating 65 **Beam Angle** 120°

AC220-240V Voltage 50-60 Hz Frequency Range CRI Ra>80 **Power Factor** >0.5

Operating Temperature -20°C ~ +50°C

SDCM <6 Class I Safety Class

Dimmable Microwave Sensor Control 2Lux/10Lux/50Lux/Disable **Daylight Threshold**

Stand-by period 0s/30s/20min

Detection range Max.10m(ceiling mounted)

Max.8m(wall mounted)

10%/20%/30%50% Standy-by dimming **Hold Time** 5s/30s/1min/10min Material Polycarbonate material

White Finish

50,000 Hours Life Span Warranty 5 Years

Applications Outdoors, Residential, Commercial, Hospitality etc.

TECHNICAL OPTIONS

12W, 21W, 24W, 36W, 55W, 66W, 80W Wattage

Color Temperature 2700K-6500K

Control Switchable, TRIAC, 1-10V, Dali Optional Emergency Kit, Microwave Sensor









